

The logo consists of a yellow horizontal bar with a blue square on the left side containing the letters 'SH' in white.

SH

CE




2014.14 (eng)

## Horizontally sliding safety window for indoor installations


Robust, horizontally sliding, electrically operated safety window for indoor or outdoor installation. The sliding window has a frame made in steel or stainless steel. The SH model is specially designed for installations in which strict demands are made on protection against assault or firearm attack. The SH model can be equipped with safety glass from 6 mm laminated glass up to 75 mm bullet-resistant glass. The sliding window is automatically locked in closed position. Operated by control switch with hold to run buttons.




## EXAMPLES OF VERSIONS



OX (O=Fixed glass, X=Sliding glass)



XO



OXLO



XOOX



XOX



OXRO



OXXO



O



XO with overhead light

## TECHNICAL INFORMATION

NAME	SH
DESCRIPTION	Robust, horizontally sliding, electrically operated window for indoor or outdoor installation. Manufactured in steel or stainless steel.
WIDTH	Customers choice.
HEIGHT	Customers choice.
FRAME THICKNESS	50 mm and above*.
WIDTH SIDE POSTS	50 mm and above*.
HEIGHT TOP PROFILE	50 mm and above*.
HEIGHT OF BOTTOM PROFILE	3 mm and above*.
GLASS FRAMES	20 mm and above*.
	<i>*Dimensions depends on glass thickness and on the safety requirements.</i>
CONSTRUCTION	Motor, transmission and automatic locking are integrated within the frame.
LOCKING	Mechanical lock which automatically locks the window in closed position. Options: interval locking, key lock.
POWER SUPPLY	230 V AC transformer.
	Options: battery backup.
CONTROL SYSTEM	Electromechanical control system with hold to run buttons. Options: S3 control system (with soft start/stop, adjustable speed, optional push-and-release buttons, optional alarm closing, etc) and various control switches.
GLASS	Safety glass with thickness 6 mm and above. For instance 6 mm E60 fire-resistant glass, 19 mm impact-resistant glass, class P7B or 75 mm bullet-resistant glass, class BR7SF.
SURFACE COATING	Powder coating in white is standard. Other surface coatings available as an option are powder coating in various colours and stainless steel cladding.
PROTECTION AGAINST FIRE	The sliding window can be equipped with fire-resistant glass, e.g. 6 mm Pyran S (E60) or 15 mm Pyrostop 30-10 (EI30). However, the design is not type-approved for installation in firewalls, and object approval would then be necessary, hence we recommend our type-approved model SV-E60 instead. Please contact our sales personnel further information.
MANUFACTURED BY	Svalson AB, Sweden

Visit [www.svalson.com](http://www.svalson.com) for more information.

*Design and material subject to change without prior notice.*

